

# AS 1040 YAK 4WD **NEW** THE PROFESSIONAL RIDE-ON FLAIL-MOWER STRONG, ROBUST, PERFORMS ON DIFFICULT TERRAIN

The AS 1040 YAK 4WD's newly developed 100 cm wide flail mowing unit is a superior alternative to the conventional rotary mowing unit.

Maximum stability and robustness – the flail mowing unit provides a wider cutting width with maximum stability. Rotary mowers with similar working widths hit their limits in extreme terrain. In the event of unseen foreign objects, the flail mower unit is at significantly less risk of damage and ensures greater operator safety.

Uniform cutting results – for visually perfect mowing results across the complete working width.



Watch our videos on:

New seat suspension with weight scale

Steep slope compatible 15 litre tank for an extended range

On-demand limited slip differential for excellent traction

Full underbody protection for steering, engine and hydrostat



Welded lashing eyes for safe transport

Easy-motion, spring-supported-cutting height adjustment

Asymmetrical flail mower deck for comfortable mowing along obstacles, surfing mowing deck allows vertical movements

Stable folding bar

Bucket seat with seat spring package for maximum comfort



Professional 2-cylinder Vanguard V-twin with durable cyclone air filter

Low back-end for allround view and optimal weight distribution

Low-pressure tyres, filled with AS-Motor tyre sealant, tubeless

Easily-accessible 12-volt battery, arranged at low position in the mower

## SAFETY FIRST

Stable folding bar, integrated safety switch in the driver seat and panic pedal for emergency stop, ensure maximum operator safety. Lashing eyes on the device enable safer transport.



## OPTIMAL ERGONOMICS

Upright sitting position, perfect steering wheel placement and legroom for operators up to 6'6" tall. Lateral deflectors protect the operator from dense growth and thorns. Bucket seat with newly



## EASY MAINTENANCE

Simple replacement of the flails and drive belt thanks to appropriate service cut-outs and openings. Fast access to all maintenance points.



## COMFORTABLE TRACTION DRIVE

Variable hydrostatic drive with one-hand drive lever, cruise control and integrated parking brake for fatigue-free work.



## EXCELLENT TRACTION

Permanent four-wheel drive with on-demand limited slip differential for the rear axle. Low pressure tyres with aggressive tread and AS-Motor tyre sealant (flat-stop).



## SURFING FLAIL MOWER DECK

The surfing mower deck adapts to rough and uneven terrain. Easy height adjustment through spring support.



## TECHNICAL SPECIFICATIONS

Model	Cutting width	Engine	Rated power	Maximum engine power	Wheel drive, speed	Cutting height adjustment	Work rate m <sup>2</sup> /h	Weight, operating dimensions	Item number
AS 1040 YAK 4WD	100 cm	B&S 4-Stroke 2-Cylinder Vanguard V-twin 3864, 627 ccm	15,5 kW (21,1 hp) at 3.600 rpm	17,2 kW (23 hp) at 3.600 rpm	Permanent all-wheel drive Hydrostat variable, Forward: 0 – 6.8 km/h Reverse: 0 – 6.3 km/h	central 30 – 110 mm, 7 x	max. 6.800	335 kg L 199 cm, W 122 cm, H 159 cm (108 cm)	G90400101

Accessories overview, see page 63



High safety against stone throw: confirmed by DLG, DIN EN 13524:2014, test report 17.00687.