



AS 2-stroke engine with EasyStart

Inflatable profile wheels  
Twin tyres available, see accessories



Engine crankshaft and blade-shaft are separated: Engine protection on impacts



Pivoting and lockable front wheels

Stable forks made of Hardox®

## AS 63 2T ES

### Mulch and mow in one step

The cross-blade system of the AS 63 Allmäher® easily cuts and chops even high growth and impresses with its outstanding cutting performance and excellent mulching result.

### Permanent traction, manoeuvrability and safety

The robust transmission with limited-slip differential ensures reliable propulsion and enables safe working even on difficult, steep terrain and on wet soil.

### Conical mower hood – perfect cut

The conical, rear-taper mower deck, as well as the pivot wheels attached outside of the cutting pattern, ensure an optimal inflow of the material that will be cut by the cross-blade. Through this design the grass is cut in a relatively upright, ideal position, with excellent cutting and mulching results.

### Steep slope power, high performance, safety and easy handling

The low weight (approx. 74 kg), good ergonomics with anti-vibration system and powerful, robust motorisation make the AS 63 the ideal mower on slopes. In this regard, the 2-stroke engine variant is extremely powerful and offers extreme climbing ability. For the first time, the redesigned 2-stroke engine is equipped with a convenient EasyStart function, and has an electronic ignition.

### Your safety is important to us!

The AS 63 has an automatic speed limiter for driving downhill, an automatic limited-slip differential and an automatic parking brake that engages when releasing the traction drive.

Watch our videos on:



### MULCHING KIT

Optional accessory for an even finer mulching result and a more uniform cutting pattern on lawn-like areas with grass up to 40 cm high.



### BLADE SYSTEM

Double-blade system for an outstanding cutting pattern and good mulching effect.



### TWIN TYRES, OPTIONAL

Twin tyres with quick-release fasteners are optionally available for steep slopes.



### VIBRATION DAMPING

Through vibration and impact damping, hand-arm vibration is reduced to a minimum.



### VARIOMATIC

The speed regulator enables variable adjustment of the drive speed.



### EASY TRANSPORT

Compact: the AS 63 is foldable for transport. Min. height: 70 cm.

Vertical service position  
Easy access for cleaning and servicing.



AS 63 4T B&S



AS 63 4T Honda



### TECHNICAL SPECIFICATIONS

Accessories overview, see page 57

Model	Cutting width	Engine	Rated power	Maximum engine power	Wheel drive, speed	Cutting height adjustment	Work rate m <sup>2</sup> /h	Weight, operating dimensions	Item number
AS 63 2T ES	61 cm	AS 2-Stroke Engine ES, 165 ccm	4,5 kW (6,1 hp) at 3.800 rpm	4,9 kW (6,7 hp) at 4.500 rpm	Variomatic 2,0 – 4,0 km/h Rear wheel drive	Front variable, rear 4-position, 50 – 100 mm	max. 2.400	77 kg L 191 cm, W 70 cm, H 99 cm	G60000102
AS 63 4T B&S	61 cm	B&S 4-Stroke Engine, 850E-Series I/C, 190 ccm	3,7 kW (5,1 hp) at 3.600 rpm	4,1 kW (5,5 hp) at 3.600 rpm	Variomatic 1,8 – 3,8 km/h Rear wheel drive	Front variable, rear 4-position, 50 – 100 mm	max. 2.300	74 kg L 191 cm, W 70 cm, H 99 cm	G60000101
AS 63 4T Honda	61 cm	Honda 4-Stroke Engine, GXV-160, 163 ccm	3,2 kW (4,3 hp) at 3.600 rpm	3,2 kW (4,3 hp) at 3.600 rpm	Variomatic 1,8 – 3,8 km/h Rear wheel drive	Front variable, rear 4-position, 50 – 100 mm	max. 2.300	83 kg L 191 cm, W 70 cm, H 99 cm	G60000103