



CUTTING HEIGHT ADJUSTMENT

Four step adjustment with transport-position and safety blade stop.



SEATING COMFORT

For the models AS 799 and AS 800 an optional seat suspension system is available. Adjustable, with gas-pressure damper.
(AS 799 from serial no. 0301 17 10 0001, AS 800 from serial no. 0300 17 10 0001)



TRANSMISSION

Variable hydrostatic transmission – forward/reverse with differential lock and rear wheel brake (Differential lock only with AS 800).



BLADE SYSTEM

Cross-blade mulching system. One cutting blade with upper mulching blade (AS 800).



BLADE SYSTEM

Closed mowing deck with single-blade system and 3-ball bearings (AS 799).

Watch our videos on:

AS 799 RIDER



AS 800 FREERIDER



AS 799 RIDER / AS 800 FREERIDER

Take a seat and get started. Our AS 799 and AS 800 provide an easy entry into our family of AS ride-on mowers.

Ambitious private users that need to mow large areas, slightly rolling terrain and around obstacles will love these machines. Grass and weeds up to 80 cm (AS 800) are no problem at all.

A low centre of gravity and an spacious seating position provide safety and comfort – even for tall people.

TECHNICAL SPECIFICATIONS

Accessories overview, see page 62

Model	Cutting width	Engine	Rated power	Maximum engine power	Wheel drive, speed	Cutting height adjustment	Work rate m ² /h	Weight, operating dimensions	Item number
AS 799 Rider	80 cm	B&S 4-Stroke Engine, Series 3 Powerbuilt, 344 ccm	6,5 kW (8,8 hp) at 3.200 rpm	7,8 kW (10,6 hp) at 3.600 rpm	Hydrostat Variable Forward: 0–8,0 km/h Reverse: 0–6,0 km/h	central 35–85 mm, 4 x	max. 6.400	203 kg L 170 cm, W 87 cm, H 96 cm	G06800102
AS 800 FreeRider	80 cm	B&S 4-Stroke Engine, Series 3 INTEK, 344 ccm	7,6 kW (10,3 hp) at 3.200 rpm	9,7 kW (13,0 hp) at 3.600 rpm	Hydrostat Variable Forward: 0–8,0 km/h Reverse: 0–6,0 km/h	central 35–85 mm, 4 x	max. 6.400	227 kg L 170 cm, W 87 cm, H 96 cm	G06800101