TORO TS90 Series



Inlet Size: 1" NPT or BSPRadius: 16,2-29,0m (53'-95')

• Operating Pressure Range: 2,8-7,0 Bar (40-100 psi)

For big open spaces, the Toro TS90 provides unparalleled features and performance into a single fully adjustable rotor.







Features & Benefits

Trujectory Adjustment from 7° to 30°

Fine tunes nozzle spray height, helps provide true headto-head coverage, and compensates for windy conditions.

Part- And Full-Circle In One Sprinkler

No need to inventory multiple models or service parts

Back Nozzle Capable

Perfect for perimeter of sports fields. Provides the flexibility for fine-tuning any watering requirement.

Ratcheting Riser

Allows you to adjust the riser position in the body with no disassembly. Simply pull up the riser and ratchet it to the precise position you want to water.

Three Nozzle Configuration

Provides better distribution uniformity, nozzle flexibility and system efficiency.

Constant-Velocity Drive

Provides reliable rotation speed – from sprinkler to sprinkler.

TurfCup[™] for Sports Fields

The optional TurfCup version seamlessly integrates into either natural grass or artificial turf sports fields, enhancing player safety, surface playability and field aesthetics.





Specifications

Dimensions

Body Height: 254mm (10")
Overall Height: 317mm (12½")
Retracted Height: 216mm (8½")

• Pop-Up Height: 100mm (4")

• Exposed Cap Diameter: 57mm (21/4")

Operating Specifications

• Radius: 16,2-29,0m (53'-95') at 25° trajectory • Flow Rate: 52,9-232,8 LPM (14.0-61.5 GPM)

Precipitation Rate: 14,2-15,2mm/hr (.56-.60"/hr.)

• Arc: Full- & Part-circle in one

- Full-circle: 360° unidirectional clockwise rotation

- Part-circle: 40°-330°

• Rotation Speed: 3 minutes ± 30 seconds

• Inlet: 1" female-threaded (NPT or BSP)

• Operating pressure range: 2,8-7,0 Bar (40-100 psi)

Additional Features

- Full set of color-coded nozzles that thread directly into the front.
- Rubber cover and below grade installation
- Check Valve standard maintains up to 3m (10') elevation
- Nozzle options: 9 main, 3 intermediate, 1 inner

Options Available

- Effluent Indicator available: part number 118-0063
- Main Nozzle Tool: 16mm (⁵/₈" hex socket or Toro Part 995-99
- Intermediate and Trajectory tool: 8mm (5/16") hex socket or Toro Part 995-105

Warranty

• 5 years

TS90 Series Model List						
Model	Description					
TS90TP-02-14	NPT, Low Flow Nozzles 1-4 Included					
TS90TP-02-58	NPT, Medium Flow Nozzles					
	5-8 Included					
TS90TP-02	TS90TP w/o TurfCup, #8 nozzle installed					
	(comes w/ #5, #6, #7 nozzles					
TS90TP-02TC	TS90TP w/ TurfCup, #8 nozzle installed					
	(comes w/ #5, #6, #7 nozzles)					
TS90TP-52	BSP, Nozzles 1-9 Included					
TS90TP-52TC	TS90TP w/ TurfCup, BSP, Nozzles 1-9					
	Included					



TS90TP Nozzle Performance Data—Metric

Nozzle Set			3,4 Bar		4,1 Bar		4,8 Bar		5,5 Bar		6,2 Bar		6,9 Bar	
Number	Main/Intermediate	Stator	Radius (m)	Flow (LPM)										
1	Yellow/Blue	102-1939 Yellow	16,2	53	16,5	58	16,8	62	16,8	66	16,5	70	17,1	74
2	Blue/Red		16,8	71	18,0	78	18,6	84	18,0	89	18,0	95	18,9	100
3	Brown/Orange			-	17,4	86	18,3	93	18,6	99	19,2	105	20,7	110
4	Orange/Orange		-	-	-	-	22,6	124	24,4	133	24,7	140	25,0	147
5	Green/Blue	102-1940 White	-	-	-	-	-	-	24,1	143	25,0	151	25,6	158
6	Gray/Blue		-	-	-	-	-	-	25,0	150	26,2	159	26,5	167
7	Black/Orange		-	-	-	-	-	-	24,4	165	26,5	175	25,6	184
8	Red/Blue		-	-	-	-	-	-	26,2	184	26,8	195	26,8	205
9	Beige/Blue	102-1941 White	-	-	-	-	-	-	25,9	208	27,7	221	29,0	233

Specifying Information—TS90TP

TS90TP <u>XX-X-X</u>										
Arc	Threads	TurfCup™		Nozzle		Optional				
TS90TP	XX			<u>X</u>		<u>E</u>				
TS90TP— TS90TP 25mm (1") Rotor with TruJectory	02—NPT	TC—TurfCup Option	1	4	7	E—Effluent Model				
	52—BSP		2	5	8					
			3	6	9					
Example: A TS90 Series sprinkler with TruJectory, NPT threads, and with an #8 nozzle would be specified as: TS90TP-02-8										

toro.com

Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801 Fax: (1) 952 887 8258

Printed in U.S.A. ©2016 The Toro Company. All Rights Reserved. GB 200-XXXXNA Electronic file only.









facebook.com twitter.com/TheToroCompany youtube.com/ToroCompanyEurope

